



TIRE MARK	COMPOUND/HARDNESS	RECOMMENDED USE	OPTIMAL TEMP.
	G8 ROCK	ROCK TERRAIN	(>60°F)
	PR SUPER SOFT ROCK	SLICK ROCK TERRAIN	(<60°F)
	MC CLAY	INDOOR CLAY	(ALL)
	M2 MEDIUM	OUTDOOR	(>90°F)
	M3 soft	INDOOR/OUTDOOR	(70°F - 90°F)
	M4 SUPER SOFT	INDOOR/OUTDOOR	(<70° F)
	S2 MEDIUM	DRY SURFACE/HIGH WEAR	(>90°F)
	S3 soft	DRY SURFACE	(70°F - 90°F)
	S4 SUPER SOFT	DRY SURFACE	(<70°F)
	<b>Z3</b> MED. CARPET	CARPET (GRAY)/ASTRO	(>90°F)
	<b>Z4</b> SOFT CARPET	CARPET (BLACK)/ASTRO	(70°F - 90°F)

WATERED SURFACE

	SUPER SOFT	SOFT	MEDIUM	FIRM		
	IDEAL SURFACE TEMPERATURE					
	WET SURFACE CONTROL			WEAR RESISTANCE		
COMPOUND	M4 M3	N				
COMPOUND	54	53	SZ			
Rock Crawling	PR	68				
Carpet				Z4 Z3		